

RSC-3M



Features :

- High-density design for space saving (cost saving)
- 4 drawers to load up to 32 hot swap drives
- Tool-less design supports quick installation and easy maintenance:
 - Tool-less 3.5" & 2.5" drive trays
 - Tool-less rear top cover
- Anti-vibration rubbers on drive trays and fans
- Silicon gaskets to absorb vibration from sides of drives
- Easy swap system fans designed to minimize rotational vibration while providing superior cooling

SPECIFICATIONS

Dimensions (W x D x H) (with chassis ears)	mm : 483 x 910 x 132		
	inches : 19 x 35.8 x 5.2		
Industry Standard	EIA-RS310D		
Material	Heavy-duty preplated SPGC cold-rolled steel		
Color	Not coated		
Cooling	Middle : 3 x 80x38mm PWM & low-power consumption hot swap fans		
Power Supply	1200W 1+1 redundant 80+ Gold		
Expansion Slots	7		
Front Panel	System power on/off and system reset		
LED Indicators	System power, LAN and Drive		
System Board	12"(W) x 13"(D) E-ATX/SSI EEB 3.6 compliant MB		
Drive Bays	Internal	3.5" hot swap	32
		2.5"	Options :
	External	2.5" hot swap	• 2 x 2.5" internal • 2 x 2.5" hot swap

Backplanes	8 x 4-port 12Gb SAS backplanes with single SFF-8643 connector on each	
Expander Board	48-port 12Gb SAS expander board with 10 SFF-8643 connectors to IOC and drives & 2 SFF-8644 connectors for connecting to JBOD	
Storage Temperature	0°C(32°F) ~ 50°C(122°F)	
Humidity	5%~95% non-condensing	
Gross Weight	(w/ PSU & Rail)	kgs : 47
		lbs : 103.6
Packaging Dimensions	(W x D x H)	mm : 1170 x 600 x 358
		inches : 46 x 23.6 x 14
Cubic Feet	8.8	
Container Load Quantity	20'	108
	40'	240
	40' H	280
Mounting	Standard	25" tool-less slide rail

• FRONT VIEW •

System power on/off and system reset



4 drawers, each loads 8 x 3.5" drives

• REAR VIEW •

7 x slots




1200W 1+1 redundant 80+ Gold

• TOP VIEW •


Options :

- 2 x 2.5" internal
- 2 x 2.5" hot-swap



32 x 3.5" hot swap & tool-less

MECHANICAL DRAWING



* Power supply is included. Motherboard is not included.