APPLICATIONS : Internet Server (Web / Mail) • CCTV Surveillance DVR • File Server • NAS / iSCSI

RMC-3N



Features :

- Front access dual USB ports
- Supports single or redundant power supply
- 2 x easy swap rear fans for superior cooling
- Rear access power supply alarm reset button (For redundant power supply only)
- 7 x full height expansion slots

SPECIFICATIONS

Dimensions (W x D x H) (with chassis ears)	mm : 482.6 x 533.4 x 133.4	
	inches : 19 x 21 x 5.25	
Industry Standard	EIA-RS310D	
Material	Heavy-duty preplated SPGC cold-rolled steel	
Color	Front Panel : Black	
Cooling	Standard	Rear : 2 x 60x25mm easy swap fans
	Option	Rear : 2 x 60x38mm fans
Power Supply	Options	300W single PSU
		460W single PSU
		510W single PSU
		460W 1+1 hot swap redundant
		500W 1+1 hot swap redundant
Expansion Slots	7	
Front Panel	Power on/off, system reset and 2 x USB ports	
LED Indicators	Power and Drive	


System Board	Up to 12"(W) x 10.5"(D) ATX/SSI CEB compliant MB		
Drive Bays	External	5.25"	6
		3.5"	1
	Internal	3.5"	1
Storage Temperature	0ºC(32ºF) ~ 50ºC(122ºF)		
Humidity	5%~95% non-condensing		
Gross Weight	(w/o PSU & Rail)	kgs : 15	
		lbs : 33	
Packaging Dimensions	(W x D x H)	mm : 590 x 715 x 306	
		inches : 23.2 x 28.1 x 12	
Cubic Feet	4.3		
Container Load Quantity	20'	220	
	40'	455	
	40' H	550	
Mounting	Options	20" slide rail	
		26" slide rail	

ENCLOSURE SOLUTIONS GROUP


RoHS Compliant

• FRONT VIEW •

Front access dual USB ports



Front bezel with key lock for security and protection



• REAR VIEW •

Rear access power supply alarm reset button



7 x slots

• TOP VIEW •


Single or redundant power supply

2 x 6038 easy swap rear fans



(Power supply is optional. Motherboard is not included.)

MECHANICAL DRAWING



Remark: All specifications and photos are subject to change without notice.

© 2015 AIC Inc. All rights reserved.