
IPC-C3SB-XP2 (RMC-3S-2)

Applications
Internet Server (Web / Mail)
File Server
NAS/iSCSI
CCTV Surveillance DVR





Features & Benefits	
1	Front bezel with lock for data security and protection
2	Four(4) external 5.25-inch optical bays supported
3	Power on/off, system reset and LEDs for HDD & LAN
4	One(1) external 3.5-inch optical bay supported
5	Front access dual USB port
6	Four(4) internal 3.5-inch HDD supported
7	PS/2 size single power supply
8	One(1) easy-swap rear fan for optimized cooling
9	Two(2) rear fan slots for upgrade
10	Rear access power supply alarm reset
11	Seven(7) PCI slots attribute to network expansion and scalability

IPC-C3SB-XP2 (RMC-3S-2)

BTO : MOQ 100		
Model Number : C3S (RMC-3S-2)		
Order Information : IPC-3SB-XP2		
Industry Standard : EIA-RS310D		
Materials : Heavy-duty preplated SPGC cold-rolled steel		
Finish :	Inside / Body : NA	
	Outside / Front : Texture coated on front panel	
Dimensions : (W x D x H)	mm : 482.6 x 530 x 133.35	
	inches : 19 x 21 x 5.25	
Cooling :	Rear: 1 x 80x25mm fan (+ optional 2 x 60x25mm - order as module)	
Power Supply :	●	Descriptions
	30X	300W ATX PFC
	46E	460W EPS-12V PFC
Expansion : 7 x PCI slots (full height, full length)		
Controls : Power on/off and system reset + 2 x USB ports		
Indicators : Power and HDD LED's		
System Board : Up to 12"(W) x 10.5"(D) ATX/SSI CEB compliant MB		

Drive Bay :	External	5.25"	4
		3.5"	1
		3.5" hot-swap	0
		2.5" hot-swap	0
	Internal	3.5"	4
	Slim CD-Rom/DVD-Rom		0
	Slim FDD		0
Temperature : 0ºC(32ºF) ~ 50ºC(122ºF)			
Humidity : 5%~95% non-condensing			
Gross Weight : 15 kgs / 33 lbs			
Packaging Dimension (W x D x H) :	mm : 580 x 710 x 300		
Cubic Feet : 4.4			
Reference Container Loading :	20'	238	
	40'	477	
	40' H	545	
Mounting Options :	BKT-2M-010-04400-G	BKT-2S-010-24200-F	
	SLR-20	SLR-26	

Mechanical Drawing

