

## 1200W



### FEATURES

- Fully Digital
- 1+1 Redundant
- Support PMBus 1.2
- High Power Density
- 80Plus Platinum certified for Module
- Active Power Factor Correction
- Application for Server, Storage, Workstation

## CPR-1222-1A1

- Dimension : 254.6 X 78 X 84mm(D x W X H)
- Total Max Power : 1200W



INPUT SPECIFICATIONS	
Input voltage	90 - 264Vac
Input frequency	47 - 63Hz

GENERAL SPECIFICATIONS	
Hold-up time	11ms @ 70% Load
Efficiency	80 PLUS Platinum certified for Module
MTBF	200,000 hours at 25 degree C

ENVIRONMENTAL SPECIFICATIONS	
Temperature	0 to 50 degree C Operating
Altitude	10,000 feet Operating
Relative humidity	0% to 85% RH Operating

OUTPUT SPECIFICATIONS					
Voltage	+3.3V	+5V	+12V	-12V	+5VSB
Regulation	±5%	±5%	±5%	±10%	±5%
Max Load	24A	40A	97.9A	0.6A	4A
Ripple & Noise	50 mVp-p	50 mVp-p	120 mVp-p	50 mVp-p	50 mVp-p

Note :  
Maximum continuous total DC output power should not exceed  
800W @ 100 - 140Vac , 1200W @ 200 - 240Vac

