



Procace Computer B.V.
 Nikkelstraat 26
 4823 AB Breda
 The Netherlands
 Tel: +31-(0)76-5423433
 Fax: +31-(0)76-5423420
 info@procace.nl
 http://www.procace.nl

Pro Computer & Industrial Case GmbH
 Krefelderstrasse 684
 D-41086 Moenchengladbach
 Germany
 Tel: +49-(0)2161-659880
 Fax: +49-(0)2161-659888
 info@pcicase.de
 http://www.pcicase.de

Pro Computer & Industrial Case Ltd.
 28 Heathfield Stacey Bushes
 Milton Keynes Bucks
 MK12 6HR
 United Kingdom
 Tel: 0870 3003388 (inside uk)
 Tel: +44-(0)870-3003388
 Fax: +44-(0)1908-220001
 sales@pcicase.co.uk
 http://www.pcicase.co.uk

Procace NZ Limited
 Unit E, no 2, Ashfield Street
 Glenfield Auckland
 New Zealand
 Tel: +64-(0)9-4413205
 Fax: +64-(0)9-4413207
 sales@procace.co.nz
 http://www.procace.co.nz

Pcicase Group (Australia) PTY LTD
 Unit D7, 27-29 Fariola Street,
 P.O. Box 6709 Silverwater, Sydney
 NSW 2128
 Australia
 Tel: +61-(2)9648-1138
 Fax: +61-(2)9648-1137
 lin@sales.com.au
 http://www.pcicase.com.au

Pcicase Group Taiwan
 3F-1, No. 42, Sec. 2
 Ho-Ping E. Road, Taipei
 Taiwan 106, R.O.C
 Tel: +886-(2)2364-3799
 Fax: +886-(2)2364-3739
 joanne@warstek.com.tw
 http://www.procace.nl

Nitro AX specifications:

- Case dimensions (WxDxH): 205 x 488 x 540mm
- Drive bays:
 5x 5.25" + 2x 3.5" front accessible
 5x 3.5" internal HDD
- Front I/O connections:
 2x USB2.0
 1x IEEE1394 (FireWire)
 1x Line output, 1x microphone input
- Supported mainboards: ATX and micro ATX
- Supported power supplies: PS/2 size
- Expansion slots: 7x full-height
- Cooling system:
 120mm rear fan (temperature controlled)
 120mm front fan (optional)
 FMB2.0 air duct
- Material: 1.0mm aluminum/SECC/SGCC

Special features:

- Removable 3.5" HDD trays
- Easy assembly 5.25" device sliding rails
- Special design flip-open door for the top optical drive
- Special air duct design to meet Intel® Prescott TASS requirements. The air duct can be adjusted in all directions. (Patent No. 0499-US-0060).
- Special front panel design, the front panel can slide along the side panel (Patent application proceeding).
- Revolving front I/O (Patent application proceeding).
- ATX Prescott ready - FMB2.0 - CAG1.1 compliant
- HDD vibration protection
- CCFL or LED light in the front panel (optional)
- Easy opening and lockable side panel

Packing and shipping info:

- Package size (WxDxH): 274 x 548 x 592mm
- NET/GROSS weight w/o PSU: 10.5 / 11.5kg
- Container content:
 20 feet: 320 PCS
 40 feet: 645 PCS
 40 feet HQ: 750 PCS

(All specifications can be changed without notice.)

NITRO AX

Super Cooling full tower case



Nitro AX Product special features



6 screw



7 Latch



8 Front Bezel



9 LED Light (Optional)



5 Removable HDD tray



2 Revolving USB



4 Removable FDD tray



3 Sliding ODD rails



1 CD/DVD Device open/close button

