

NOAH



MINI-ITX

- Aluminium front panel
- Riser card option
- Desktop stand included
- 80W power supply
- 3.5" HDD bay

**MINI
ITX
SOLUTION**

CRS

Features:

Aluminium front panel
Low noise cooling
Riser card option
Stand for vertical use included

Versatile HDD drive bay
Slim optical drive bay
Hidden reset button
80W PSU kit included

Specifications:

Dimensions (WxHxD): 202 x 97 x 273mm
Materials: SECC body, ABS plastic/aluminium front
Supported mainboards: mini-ITX (17x17cm)
Drive bays: 3.5"/2.5" HDD bay, slim-optical bay
Cooling: low-noise 80mm fan
Indicators: power LED (blue) and HDD LED (red)
Switches: power and reset
Expansion slots: PCI 32-bit with an optional riser card
Front connections: 2x USB, audio and FireWire (IEEE1394)

Power supply specifications:

Adapter input: 100~240V AC, 47~63Hz, 1.2A RMS max.
Adapter output: 12V DC, 6.6A max. (80W)
DC board power: 90W max.
DC board input: 11.4 ~ 12.6V DC
DC board output: 3.3V 7A max. 5V 7A max. 12V 2A max.
-12V 0.1A max. 5Vsb 1A max.
MTBF: 150.000 hours



Procase Computer BV
Nikkelstraat 28
4823 AB Breda
The Netherlands
www.procase.nl
info@procase.nl
Tel. +31-(0)76-5423433

PCI Case GmbH
Krefelderstrasse 773
D-41066 Moenchengladbach
Germany
www.pccase.de
info@pccase.de
Tel. +49-(0)-2161-6598880

PCI Case Ltd
28 Heathfield, Stacey Bushes
Milton Keynes, Bucks, MK12 6HR
United Kingdom
www.pccase.co.uk
sales@pccase.co.uk
Tel. +44-(0)1908-321000 (int.)
Tel. 0870-3003388 (UK)

Procase NZ Limited
Unit E, no.2, Ashfield Road
Glenfield Auckland
New Zealand
www.procase.co.nz
sales@procase.co.nz
Tel. +64-(0)9-4413205

PCI Case Group Australia Ltd.
Unit D7,27-29, Fariola Street
Silverwater, Sydney
NSW 2128 Australia
www.pccase.com.au
sales@pccase.com.au
Tel. +61-2-9648-1138

PCI Case Group Taiwan
3F, No.152, Sec 1, Jianguo S. Rd.
Taipei, Taiwan 106, R.O.C.
www.wamtek.com.tw
info@pccase.com.tw
Tel. +886-(2)2771-9558

